

# ADHESIVE PRODUCT SPECIFICATION

## GIA1048

### DESCRIPTION:

Versatile packaging hot melt exhibiting high hot tack and excellent adhesion to many difficult to adhere surfaces. Bonds exhibit excellent high and low temperature performance.

### PHYSICAL PROPERTIES:

TYPE	: Synthetic Resin
VISCOSITY	: 1000 $\pm$ 150 cps @ 350°F
OPEN TIME	: Medium
SPEED OF SET	: Medium
APPLICATION TEMPERATURE	: 350°F $\pm$ 25°F
SOFTENING POINT	: 158°F $\pm$ 2.0°F
COLOR	: Amber
SHELF LIFE	: One year
FDA STATUS	: Meet composition requirements of indirect food Additives Regulation 21 CFR 175.105 "Adhesives".

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

REV. 9/2004

Glue Machinery Corporation™  
707 East Ordnance Road, Suite 401, Baltimore, MD 21226  
888-202-2468 · Fax: 410-761-5127 · E-mail: [info@gluemachinery.com](mailto:info@gluemachinery.com)  
[www.gluemachinery.com](http://www.gluemachinery.com)



