

# ADHESIVE PRODUCT SPECIFICATION

## GIA1076

### **DESCRIPTION:**

An elastometric hot melt with high peel values to be used as a “release type” hot melt adhesive.

### **PHYSICAL PROPERTIES:**

TYPE	: Synthetic Polymer
VISCOSITY	: At 350° - 450° cps $\pm$ 50
SPEED OF SET	: Slow (Pressure Sensitive)
APPLICATION TEMPERATURE	: 325° – 350°F
SOFTENING POINT	: 155°F
COLOR	: Very, very light
SHELF LIFE	: One year
FDA STATUS	: Meet composition requirements of indirect food Additives Regulation 21 CFR 175.105 “Adhesives”.

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

1/5/2005

**Glue Machinery Corporation™**  
707 East Ordnance Road, Suite 401, Baltimore, MD 21226  
888-202-2468 • Fax: 410-761-5127 • E-mail: [info@gluemachinery.com](mailto:info@gluemachinery.com)  
[www.gluemachinery.com](http://www.gluemachinery.com)