

ADHESIVE PRODUCT SPECIFICATION

GIA1042

DESCRIPTION:

A medium setting hot melt used for adhering difficult to bond substrates. Good low temperature bonds.

PRINCIPAL USES:

GIA1042 is used for difficult to bond surfaces.

PHYSICAL PROPERTIES:

TYPE	: Formulated hot melt
VISCOSITY	: 1200 cps @ 350°F
OPEN TIME	: Long
SPEED OF SET	: Medium-Slow
SOFTENING POINT	: 190°F
APPLICATION TEMPERATURE	: 350°F ± 25°F
COLOR	: Yellow - Tan
SHELF LIFE	: One year
APPLICATORS	: Nozzle extrusion or wheel
FDA STATUS	: Meet composition requirements of indirect food Additives Regulation 21 CFR 175.105 "Adhesives".

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

9/2004

Glue Machinery CorporationTM
4234 Boston Street, Baltimore, MD 21224
888-202-2468 · Fax: 410-761-5127 · E-mail: info@gluemachinery.com
www.gluemachinery.com

