

ADHESIVE PRODUCT SPECIFICATION

HOT MELT PRESSURE SENSITIVE ADHESIVE

GIA1045

DESCRIPTION:

Bag containing adhesive is a component of the adhesive and does not need to be separated from the adhesive

A low viscosity permanent pressure sensitive hot melt adhesive with aggressive tack and excellent adhesion and machine-ability. A packaging and assembly adhesive, GIA1045 is widely used in magazine and web-fed labeling systems for foam, plastic, wood and metal product bonding.

PHYSICAL PROPERTIES:

TYPE	: Formulated hot melt
VISCOSITY	: 700 cps @ 300°F
OPEN TIME	: Always Open
SPEED OF SET	: Slow
SOFTENING POINT	: 150°F
APPLICATION TEMPERATURE	: 275°F - 325°F
COLOR	: Light Amber
SHELF LIFE	: One year
FDA STATUS	: Meet composition requirements of indirect food Additives Regulation 21 CFR 175.105 "Adhesives".

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

Glue Machinery Corporation™
4234 Boston Street, Baltimore, MD 21224
888-202-2468 · Fax: 410-761-5127 · E-mail: info@gluemachinery.com
www.gluemachinery.com