

MATERIAL SAFETY DATA SHEET

Glue Machinery Corporation™
4234 Boston Street
Baltimore, Maryland 21224

IDENTITY (As Used on Label)
GBA1015 Adhesive

Chemical Name/Family
N/A

SECTION 1

Manufactured for
Glue Machinery Corporation™
4234 Boston Street
Baltimore, Maryland 21224

Emergency Telephone Number
(410)761-2727
Telephone Number for Information
(410)761-2727

Date Prepared May 20, 2008

SECTION 2: HAZARDOUS INGREDIENTS IDENTITY

None
Non-hazardous ingredients - 100%

SECTION 3: PHYSICAL DATA

Boiling Point	- N/A	Specific Gravity	- (75° F) - 0.92
Vapor Pressure	- N/A	Melting Point	- 197°F
Vapor Density	- N/A	Evaporation Rate	- N/A
Solubility in Water	- Insoluble		
Appearance and Odor	- Clear and no odor		

SECTION 4: FIRE AND EXPLOSION HAZARD DATA

Dot Category - Non Flammable
Flash Point - 450°F
Extinguishing Media - CO₂
Will remain hot when molten for some time.

Special Fire Fighting Procedures - None
Unusual Fire and Explosion Hazards - None

SECTION 5: HEALTH HAZARD DATA

Main Route of Entry - Inhalation of Plasticizer Vapors
Target Organs - Skin can be severely damaged from contacting molten adhesive
Health Hazards (Acute and Chronic) - None

Effects

Oral - Irritation
Respiratory - Irritation
Dermal - Slight Irritation, possibly acne-like reactions due to oil in pores

FIRST AID:

COOL AFFECTED AREA IMMEDIATELY, OBTAIN MEDICAL ASSISTANCE. DO NOT ATTEMPT TO REMOVE COOLED ADHESIVE FROM SKIN A SEVERE DAMAGE COULD RESULT

SECTION 6: REACTIVITY DATA

Stability - Stable
Hazardous decomposition or by-products - Carbon monoxide
Conditions to avoid - Temperatures over 400°F may cause resin degradation
Hazardous polymerization - Cannot occur

SECTION 7: SPILL OR LEAK PROCEDURES

Spill - Sweep up raw materials and dispose to eliminate slip hazard, allow molten material to cool.
Scrape up and dispose
Waste Disposal Method - In accordance with local regulations

SECTION 8: PROTECTIVE EQUIPMENT TO BE USED

Ventilation - Yes, do not use in confined spaces
Protective Gloves - Yes
Eye Protection - Yes

SECTION 9: PRECAUTIONS OR OTHER COMMENTS

Storage and Handling - Store in cool dry place, Optimum Temperature 70°F

SECTION 10: OTHER COMMENTS

NFPA Hazard Classification

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None