

ADHESIVE PRODUCT SPECIFICATION

GIA1048

DESCRIPTION:

Versatile packaging hot melt exhibiting high hot tack and excellent adhesion to many difficult to adhere surfaces. Formulated to be used in packaging operations.

FEATURES:

- High hot tack
- Excellent adhesion to many difficult to adhere surfaces
- Superior high and low temperature performance

PHYSICAL PROPERTIES:

TYPE	: Modified Synthetic Resin
VISCOSITY	: 1000 \pm 150 cps @ 350°F
OPEN TIME	: Medium
SPEED OF SET	: Medium
APPLICATION TEMPERATURE	: 350°F \pm 25°F
SOFTENING POINT	: 158°F \pm 2.0°F
COLOR	: Amber
SHELF LIFE	: One year
FDA STATUS	: Meets composition requirements of indirect food Additives Regulation 21 CFR 175.105 "Adhesives".

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

09/17/2010

Glue Machinery Corporation™

4234 Boston Street, Baltimore, MD 21224

888-202-2468 · Fax: 410-761-5127 · E-mail: info@gluemachinery.com

www.gluemachinery.com