

ADHESIVE PRODUCT SPECIFICATION

GIA1051

DESCRIPTION:

GIA1051 is a hot melt with excellent hot tack. It was designed to adhere to many difficult substrates with a wide range of adhesion.

USES:

Used in packaging, bookbinding, display, product assembly and other miscellaneous operations.

FEATURES:

- Excellent hot tack
- Extended open time
- Exhibits flexible bond

PHYSICAL PROPERTIES:

TYPE	: EVA Modified Thermo Plastic
VISCOSITY	: 2,200 cps @ 350°F
SPEED OF SET	: Slow
SOFTENING POINT	: 166°F
COLOR	: Light amber
APPLICATION TEMPERATURE	: 325°F - 375°F
SHELF LIFE	: Twelve (12) months
FDA STATUS	: FDA STATUS: Meets composition requirements of indirect food additives. Regulation 21 CFR 175.105 "Adhesives".

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. 03/03/2016

Glue Machinery Corporation™

4234 Boston Street, Baltimore, Maryland 21224

888-202-2468 • Fax: 410-761-5127 • E-mail: info@gluemachinery.com

www.gluemachinery.com