

ADHESIVE PRODUCT SPECIFICATION

GIA1060 – APAO Polyolefin Hot Melt Adhesive

DESCRIPTION:

Hot melt adhesive that exhibits excellent tack with an extended open time. GIA1060 was formulated to adhere to a variety of difficult substrates at elevated temperatures. It is recommended for most foam to foam applications.

Bag containing adhesive is a component of the adhesive and does not need to be separated from the adhesive.

USES:

Specifically formulated to bond a variety of difficult substrates.

FEATURES:

- Excellent hot tack
- Extended open time
- High heat resistance

PHYSICAL PROPERTIES:

TYPE:	Modified synthetic resin
VISCOSITY:	3,700 – 4,700 cps @ 350°F
SPEED OF SET:	Slow
APPLICATION TEMPERATURE:	340° - 375°F
COLOR:	White
SOFTENING POINT:	271°F
OPEN TIME:	Long
SHELF LIFE:	Twelve (12) months
FDA STATUS:	Meets composition requirements of indirect food additives. Regulation 21 CFR 175.105 “ADHESIVES”.

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. 05/31/2017

Glue Machinery CorporationTM

4234 Boston Street, Baltimore, MD 21224

888-202-2468 • Fax: 410-761-5127 • E-mail: info@gluemachinery.com

www.gluemachinery.com