

ADHESIVE PRODUCT SPECIFICATION

GTA8000

SPECIFICATION:

Removable Hot Melt Adhesive

DESCRIPTION:

A hot melt pressure sensitive adhesive designed as a general purpose removable.

PHYSICAL PROPERTIES:

FORM	: Pillows
TYPE	: Elastomeric
VISCOSITY	: 950cps \pm 200 at 325°F
APPLICATION TEMPERATURE	: 300 - 350°F
SOFTENING POINT	: 172°F / 78°C
COLOR	: 1 – 2 (Gardner) Lovidbond 2000, Neat
CLEANUP	: Purge compound
FDA STATUS	: Conforms with FDA regulation 21CFR 175.105 for indirect food contact

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision.

1/16/2016

Glue Machinery Corporation™

4234 Boston Street, Baltimore, MD 21224

888-202-2468 · Fax: 410-761-5127 · E-mail: info@gluemachinery.com

www.gluemachinery.com