

ADHESIVE PRODUCT SPECIFICATION

G89A77-001 / ChampStick™ Max

SPECIFICATION:

High Tack Glue Stick

DESCRIPTION:

G89A77-001 / ChampStick™ Max is a high performance, high tack glue stick especially suitable for packaging applications where aggressive tack and long open-time is required. This stick is also suitable for bonding of plastic – plastic.

PHYSICAL PROPERTIES:

Form:	Rods – 11 mm diameter
Color:	Translucent to Pale Yellow
Surface Touch:	Light Ambient Tack
Softening Range:	176°F - 185°F (80°C – 85°C)
Application Temperature:	Use minimum 60W applicator gun
Specific Gravity:	0.96
Water Absorption:	Negligible
Stability:	20 Hrs. at 302°F (150°C)
Viscosity:	30,000 cPs +- 20% @ 320°F (160°C)
Shelf Life:	18 months @ < 86°F (30°C)
Open Time:	Long

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. 12/05/2016

Glue Machinery Corporation™

4234 Boston Street, Baltimore, MD 21224

888-202-2468 · Fax: 410-761-5127 · E-mail: info@gluemachinery.com

www.gluemachinery.com