

ADHESIVE PRODUCT SPECIFICATION

GBA1015

DESCRIPTION:

GBA1015 is an extremely low viscosity removable/peelable pressure sensitive adhesive. It boasts low viscosity, moderate tack, and can be used for mailers, inserts and tipping. It is formulated to provide negligible bleeding or staining on most types of paper substrates.

PHYSICAL PROPERTIES:

Application Temperature	: 300 - 350° F
Tack Level	: Low to Moderate
Suggested Running Temperature	: 350° F
Viscosity 350° F	: 950 cPs (+/-) 10%
Softening Point	: 197° F
Gardner Color	: 1-2 Max
Product Form	: Pellets averaging 1/4" in diameter. Drums upon request.
Packaged & Shipped	: 25 lb. corrugated boxes palletized and shrink wrapped for a pallet sum of 60 boxes (1,500 lbs). Drums equal 350 lbs each for a pallet total of 1,400 lbs. (4 drums)
Shelf Life	: One year

Components contained in this product conform to USDA and FDA regulations for use in food packaging, as stated in the Federal Food and Drug and Cosmetic Act, Title 21 under section 175-105. This guarantee is also intended to comply with USDA's "Policy Governing Inspection of Packaging Materials".

Our personnel are available to help purchasers obtain best results from our products and recommendations are based on tests and information believed to be reliable. However, since we have no control over the conditions under which our products are transported to, stored, handled, or used by purchasers, all recommendations and sales are made on condition that we will not be held liable for any damages resulting from their use. No representative of ours has any authority to waive or change this provision. 6/24/2019

Glue Machinery Corporation™

4234 Boston Street, Baltimore, MD 21224

888-202-2468 · Fax: 410-761-5127 · E-mail: info@gluemachinery.com
www.gluemachinery.com